

RS-232C Communication Protocol - for all models other than IIZWP32-H01

DVB-T Models (Full-HD) Suits models – 42H, 42F, 47F, 52F, 57F and 70F

Communication Parameters	
Baud rate	9600 bps
Data length	8 bits
Parity	None
Stop bit	1 bit
Communication code	ASCII code
Flow Control	None

RS232 CODES		RS 232 FUNCTION
CHNL	0~99	Channel Number
MUTE	99	Toggle On / Off
	0	Mute On
	1	Mute Off
PWRX	None	Toggle On / Off
POWR	1	Power On
	0	Power Off
SRCE	None	Source OSD window
ITVA	None	INPUT TV Analog
IDVB	None	INPUT TV Digital
ISCT	1~2	INPUT Scart 1~2
ICMP	None	INPUT Composite Video
ISVD	None	INPUT S-Video
IRGB	None	INPUT Component
IHDM	1~3	INPUT HDMI 1~3
IAPC	None	INPUT PC Analog RGB
UPXX	None	Increase channel by 1 and other functions
DOWN	None	Decrease channel by 1 and other functions
LEFT	None	Increase volume by 1 and other functions
RGHT	None	Decrease volume by 1 and other functions
ENTR	None	Select menu item
SLCT	None	Select menu item
MENU	None	Menu
EXIT	None	Exit
INFO	None	Information
DUAL	None	Change Sound Format
ASPC	1	WIDE
	2	PANORAMA
	3	4:3
	4	ZOOM
	5	AUTO
	6	14:9
	7	AUTO WIDE
VOLM	None	Volume 100
	0~100	Volume 0~100

Command Syntax

Command + Number or None ex) CHNL90 , POWR1 , IAPC , ITVA , MUTE1 , MUTE0

*** No space between command and number ***